

<h2 style="margin: 0;">Filtri</h2> <h3 style="margin: 0;">Strainers ANSI 150 – 300 - 600</h3>	<p>Type</p> <p><b>FYAN</b></p>
---	--------------------------------

ANSI Class 150:fig A15  
 ANSI Class 300:fig A30  
 ANSI Class 600:fig A60



flanged ends to ANSI B 16.5  
 face to face to ANSI B 16.10

**pressione/temperatura:**  
**pressure/temperature**  
**rating:**

		- 20/+ 100 °F	200 °F	400 °F	500 °F	700 °F	750 °F
		- 29/+ 38 °C	90 °C	200 °C	260 °C	370 °C	400 °C
class 150	psi	285	260	200	170	110	95
	bar	20	18	14	11,5	7,5	6,5
class 300	psi	740	665	635	600	535	505
	bar	51	46	44	41,5	37	35
class 600	psi	1480	1350	1270	1200	1065	1010
	bar	104	95	89	84	75	71

**materiali:**  
**materials**

body cast steel ASTM A 216 WCB  
 cover forged steel ASTM A 105  
 screen stainless steel AISI-304 perforation 0,6 mm  
 drain plug stainless steel AISI-304

**Su richiesta. On request:** Cestello con altri tipi di perforazione/screen with other perforations  
 ANSI Class 900 and 1500  
 Altri materiali tipo/other materials p.e.:  
 ASTM A351 CF8 - ASTM A350 LF2

**Dimensioni (mm):**  
**Dimensions (mm):**




Fig. A15  
Class 150

Fig. A30  
Class 300

Fig. A60  
Class 600

DN		A		L		H		E	F	wt (kg)
inches	mm	inches	mm	inches	mm	inches	mm	mm	mm	
2	50.8	6	152	8	203	8 1/8	205	155	55	12
3	76.2	7 1/2	191	9 1/2	241	10 1/16	255	186	80	24
4	101.6	9	229	11 1/2	292	11 13/16	300	227	106	40
6	152.4	11	280	16	406	15 3/8	390	275	155	71
8	203.2	13 1/2	343	19 1/2	495	19 5/16	490	371	205	120
10	254	16	406	24 1/2	622	21 1/16	550	442	255	175
12	304.8	19	483	27 1/2	699	25 7/16	640	510	305	260
2	50.8	6 1/2	165	10 1/2	267	9 1/4	235	155	55	22
3	76.2	8 1/4	210	12 1/2	318	11 1/4	285	198	86	37
4	101.6	10	254	14	356	12 5/8	320	238	106	56
6	152.4	12 1/2	318	17 1/2	445	16 9/16	420	330	155	116
8	203.2	15	381	22	559	18 7/8	480	371	205	180
10	254	17 1/2	445	24 1/2	622	23 5/8	600	447	255	271
12	304.8	20 1/2	521	28	711	27 1/8	690	523	305	400
2	50.8	6 1/2	165	11 1/2	292	8 1/4	210	155	55	23
3	76.2	8 1/4	210	14	356	10 1/4	260	186	86	43
4	101.6	10 3/4	273	17	432	12 3/16	310	238	106	75
6	152.4	14	356	22	559	15 3/8	390	295	155	160
8	203.2	16 1/2	419	26	660	18 1/2	470	335	210	270